

**RECEIVED  
CENTRAL FAX CENTER****AUG 21 2007**

Application Serial No: 10/530,725  
Responsive to the Office Action mailed on: February 21, 2007

### IN THE CLAIMS

#### Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. (Currently Amended) An analyzing method comprising:  
a first detection step for irradiating light onto a reaction system to detect a response from the reaction system as a first detection result, the reaction system including a sample liquid and a reagent;  
a second detection step for irradiating light onto a reference board to detect a response from the reference board as a second detection result, the response from the reference board ~~being dependent on~~ varies continuously with varying wavelength; and  
a calculation step for calculating a concentration of a specific component in the sample liquid based on the first and second detection results.
2. (Original) The analyzing method according to claim 1, wherein the calculation step includes selecting a most suitable calibration curve from a plurality of pre-created calibration curves based on the second detection result, and calculating the concentration of the specific component based on the selected calibration curve and the first detection result.
3. (Original) The analyzing method according to claim 1, wherein the calculation step further includes correcting the first detection result based on the second detection result, and calculating the concentration of the specific component based on the correction and the calibration curve.
4. (Original) The analyzing method according to claim 1, wherein the calculation step further includes performing primary calculation of the concentration of the specific component, and obtaining a final calculated value by correcting the primary calculated

Application Serial No: 10/530,725  
Responsive to the Office Action mailed on: February 21, 2007

value.

5. (Original) The analyzing method according to claim 1, wherein at least one of the responses in the first and second detection steps is detected as an amount of regular reflection light, transmitting light, or scattering reflection light.

6. (Currently Amended) An analyzing device comprising:

a light irradiator for irradiating light toward a reaction system and a reference board, the reaction system including a sample liquid and a reagent;

a detector-detecting unit arranged to face the reaction system and the reference board for detecting a first response from ~~[[a]] the reaction system under light irradiation from the light irradiator, the reaction system including a sample liquid and a reagent, the detector-detecting unit~~ detecting a second response from ~~[[a]] the reference board under light irradiation from the light irradiator, the second response from the reference board being dependent on~~ varies continuously with varying wavelength; and

a calculator connected to the detecting unit for calculating a concentration of a specific component in the sample liquid based on the first and second responses.

7. (Original) The analyzing device according to claim 6, further comprising:

a storage for storing a plurality of calibration curves each representing relationship between a first detection result corresponding to the first response and the concentration of the specific component; and

a selector for selecting a most suitable calibration curve for calculation from the plurality of calibration curves based on a second detection result corresponding to the second response,

wherein the calculator calculates the concentration of the specific component based on the calibration curve selected by the selector and the first detection result.

8. (Original) The analyzing device according to claim 6, wherein the calculator corrects the first detection result corresponding to the first response based on the second detection result corresponding to the second response, and then calculates the

Application Serial No: 10/530,725  
Responsive to the Office Action mailed on: February 21, 2007

concentration of the specific component based on the correction.

9. (Original) The analyzing device according to claim 6, wherein the calculator performs primary calculation of the concentration of the specific component based on the first detection result, and then calculates a final value by correcting the primary calculated value.

10. (Original) The analyzing device according to claim 6, further comprising a controller for controlling timing for detection of the second response at the detector.

11. (Original) The analyzing device according to claim 10, wherein the controller controls the detector for detecting the second response before or after the detection of the first response, or simultaneously with the detection of the first response.

12. (Original) The analyzing device according to claim 10, wherein the controller controls the detector for detecting the second response upon start-up of the analyzing device.

13. (Original) The analyzing device according to claim 6, wherein at least one of the first and second responses is detected as an amount of regular reflection light, transmitting light, or scattering reflection light.

14. (Withdrawn-Currently Amended) A method of producing an analyzing device which comprises a light irradiator for irradiating light onto a reaction system which includes a sample liquid and a reagent, a detector for detecting a response from the reaction system under light irradiation, a calculator for calculating a concentration of a specific component in the sample liquid based on the detection at the detector, and a storage for storing information necessary for calculation as to the specific component, the method comprising:

a detection step for irradiating light from the light irradiator onto a reference board to detect a response from the reference board under light irradiation for

Application Serial No: 10/530,725

Responsive to the Office Action mailed on: February 21, 2007

determining a light emitting state of the light irradiator, the response from the reference board ~~being dependent on~~ varies continuously with varying wavelength; and

a storage step for storing the light emitting state in the storage as information for use in calculation at the calculator.

15. (Withdrawn) The analyzing device production method according to claim 14, further comprising

a calibration curve selecting step for selecting a calibration curve corresponding to the light emitting state, from a plurality of calibration curves representing relationship between the detection result at the detector and the concentration of the specific component, based on the detection in the detection step,

wherein the storage step includes storage of the calibration curve selected in the calibration curve selecting step for use in calculation at the calculator.

16. (Withdrawn) The analyzing device production method according to claim 14, wherein the light emitting state is detected as a peak wavelength of emitted light in the detection step, the peak wavelength being stored by the storage in the storage step.

17. (Withdrawn) The analyzing device production method according to claim 14, wherein the reference board used in the detection step is incorporated in the analyzing device beforehand.

18. (Withdrawn) The analyzing device production method according to claim 14, wherein the reference board used in the detection step is prepared separately from the analyzing device.